

PONY Series



VARIOUS INVERTER DC ARC WELDING MACHINE FROM PORTABLE TO (AAAAA) !

High speed of response by the high-speed switching control make easy arc start and welding of high quality

Optimum arc start

Easy operability and portability

Compact size, light weight, power-saving design

Adoption of circuit of electric shock prevention and power protection



Recommended welding consumables (HYUNDAI)

▶ SMAW S-6013.LF, S-7016.H, S-7018.1H

MODEL		2160H	2180H	2200H	2230H	2300H	2400H	2500H
TYPE		MMA						
RATED POWER	kVA	5	6.5	8	11	14	18	25
INPUT VOLTAGE	V	1P 220V			1P, 3P 220V, 380V, 440V			
FREQUENCY	Hz	50 / 60						
RATED OUTPUT CURRENT	A	160	180	200	230	300	400	500
RATED OUTPUT VOLTAGE	V	26.5	27.5	28	30	32	36	40
RATED OUTPUT CURRENT RANGE	A	20~160	20~180	20~200	20~230	20~300	20~400	20~500
RATED OUTPUT VOLTAGE RANGE	V	20~26.5	20~27.5	20~28	20~30	20~32	20~36	20~40
MAX. OPEN CIRCUIT VOLTAGE	V	72		73		90		
DUTY CYCLE	%	60						
WEIGHT	kg	8.2	11.2	13	15.3	20	58	76
DIMENSION (WxDxH)	mm	130x390x210	180x400x220	185x450x245	285x440x215	305x450x360	390x520x620	410x600x740

▶ In accordance with HYUNDAI WELDING policy to make continuing improvements, design and/or specifications are subject to change without notice or any obligation on the part of manufacturer.